

**3in1: COOLING - DRYING - VENTILATION** 













## **TECHNICAL DATA**

MODEL	KPPH-09HRN29
Cooling capacity [kW]	2.6
Energy class	A
EER	2.6
Power input [W]	1000
Operation current [A]	4.35
Air flow [m³/h]	295/195
Operating temperature [°C]	17÷35
Sound pressure level dB[A]	51.9/46.9
Net dimensions w/d/h [mm]	355x345x703
Transport dimensions w/d/h [mm]	400x390x880
Net weight [kg]	25.3
Transport weight [kg]	28.1
Electric power supply [V, Hz, Ph]	220÷240, 50
Refrigerant	R290
Amount of refrigerant [kg]	0.17
Amount of removed moisture [I/h]	2.12



# MOST IMPORTANT FUNCTIONS







#### **SELF-DIAGNOSIS**

The air conditioner monitors its operation and switches off when a malfunction or failure is detected. The error code is displayed on the control panel of the indoor unit.



#### **TIMER**

The timer enables setting the time of automatic switching on and off the air conditioner.



### **SLEEP FUNCTION**

Within two hours, the unit increases the set temperature by 1°C per hour, and the fan is running at low speed. This reduces electric energy consumption and provides the best comfort for the user.



#### **AUTOMATIC RESTART**

During a power outage, the air conditioner remembers the last settings and restores them once the power is resumed. It does not require reprogramming of the unit after each power outage.



#### **EVAPORATION OF CONDENSATE**

The condensed water is transferred to the condenser where it mostly evaporates. As a result, the big condensate tank is not required.